

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : HYDRO PELLETT 3500
Material number : 024072HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guenthersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Skin corrosion/irritation, Category 3, H316
Short-term (acute) aquatic hazard, Category 3, H402
Long-term (chronic) aquatic hazard, Category 3, H412

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

GHS-Labeling

Signal word : Warning

Hazard statements : H316: Causes mild skin irritation.
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
Response:
P332 + P317 If skin irritation occurs: Get medical help.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label
Other hazards which do not result in classification

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0)	;2;H315 ;1;H318 Aquatic Acute;2;H401	3 - 10

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

		Aquatic Chronic;2;H411	
--	--	---------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
 No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
 If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO₂), Water, Foam**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Use personal protective equipment.
Evacuate personnel to safe areas.
Use personal protective equipment.

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Avoid dust formation.
Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Do not use a vacuum cleaner.

Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

This information is not available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid dust formation. Routine housekeeping should be
instituted to ensure that dusts do not accumulate on surfaces.
Store away from heat.

Avoid contact with skin and eyes. For personal protection see
section 8. Smoking, eating and drinking should be prohibited
in the application area. Dispose of rinse water in accordance
with local and national regulations.

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation
at places where dust is formed.

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Peak-limit: excursion factor (category)		2;(II)			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
2,2',2''-nitrilotriethanol	102-71-6	AGW (Inhalable fraction)	1 mg/m ³	2018-06-07	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m ³	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m ³	2012-07-01	
aluminium powder	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

(stabilised)					
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable particulate matter)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium	7429-90-5	TWA	1 mg/m3	2013-03-01	

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

powder (stabilised)		(Respirable particulate matter)			
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m ³	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m ³	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m ³	2017-10-02	
2,2',2''- nitrilotriethan ol	102-71-6	TWA	5 mg/m ³	2013-03-01	
2,2',2''- nitrilotriethan ol	102-71-6	PEL	5 mg/m ³	2014-11-26	
stearic acid	57-11-4	TWA	10 mg/m ³	2016-03-01	
stearic acid	57-11-4	TWA (Inhalable particulate matter)	10 mg/m ³	2018-03-20	
stearic acid	57-11-4	TWA (Respirable particulate matter)	3 mg/m ³	2018-03-20	

8.2 Exposure controls
Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Protective gloves

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
 The exact break through time can be obtained from the protective glove producer and this has to be observed.

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing

: Dust impervious protective suit
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 Breathing apparatus with filter.
 P1 filter

Environmental exposure controls

General advice :

: Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

:

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: pellets
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

Self-Accelerating decomposition temperature (SADT)	: No data available
Self-heating substances	: No data available
Heat of combustion	: No data available
Impact sensitivity	: No data available
Surface tension	: No data available
Conductivity	: No data available
Sublimation point	: No data available
Molecular weight	: No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Hazardous reactions : Contact with acids and alkalis may release hydrogen.
Stable under recommended storage conditions.
Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Water

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

No data available

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Serious eye damage/eye irritation**Product**

Result: No eye irritation

Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

Further information**Product**

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****Phosphoric acid, C11-14-isoalkyl esters, C13-rich (154518-38-4) :**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6,31 mg/l
aquatic invertebrates Exposure time: 48 hToxicity to algae : EC50 (algae): 150 mg/l
Exposure time: 72 h**12.2 Persistence and degradability**

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

HYDRO PELLETT 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group**

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

14.5 Environmental hazards**14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (aluminium powder (stabilised)) (Phosphoric acid, C11-14-isoalkyl esters, C13-rich)

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

HYDRO PELLET 3500

Version 3.0

Revision Date 22.09.2021

Print Date 06.04.2022

SECTION 16: Other information**Full text of H-Statements**

H228 : Flammable solid.
H315 : Causes skin irritation.
H316 : Causes mild skin irritation.
H318 : Causes serious eye damage.
H401 : Toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.