

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : METALURE A-41010 AE
Material number : 051106IA0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guntersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Serious eye damage/eye irritation, Category 2A, H319
Specific target organ toxicity - single exposure, Category 3,

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

Central nervous system, H336

GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label

Identification
ethyl acetate
acetone

CAS-No.
141-78-6
67-64-1

SECTION 3: Composition/information on ingredients

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	60 - 100
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 30
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	1 - 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

	If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

for firefighters

necessary.

Further information

: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

: Evacuate personnel to safe areas.
 Use personal protective equipment.
 Ensure adequate ventilation.
 Remove all sources of ignition.
 Evacuate personnel to safe areas.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions

: Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: Use mechanical handling equipment.
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

local / national regulations (see section 13).
 Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m ³	2017-06-08	DE TRGS 900
Peak-limit: excursion factor (category)	2;(l)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European				

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

		Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
acetone	67-64-1	TWA	500 ppm 1 210 mg/m ³	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2015-03-02	DE TRGS 900
Peak-limit: excursion		2;(I)			

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

factor (category)	
Further information	Commission for dangerous substances Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). European Union (The EU has established a limit value: deviations in value and peak limit are possible) When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	2013-10-08	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	1997-08-04	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	1989-01-19	
ethyl acetate	141-78-6	PEL	400 ppm 1 400 mg/m ³	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (respirable)	5 mg/m ³	2012-07-01	

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

powder (stabilised)		fraction)			
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable particulate matter)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m ³	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable particulate matter)	1 mg/m ³	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m ³	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m ³	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m ³	2017-10-02	
acetone	67-64-1	TWA	250 ppm	2016-03-01	
acetone	67-64-1	STEL	500 ppm	2016-03-01	
acetone	67-64-1	TWA	250 ppm 590 mg/m ³	2013-10-08	
acetone	67-64-1	TWA	1 000 ppm 2 400 mg/m ³	1997-08-04	
acetone	67-64-1	TWA	750 ppm 1 800 mg/m ³	1989-01-19	
acetone	67-64-1	STEL	1 000 ppm 2 400 mg/m ³	1989-01-19	
acetone	67-64-1	STEL	750 ppm 1 780 mg/m ³	2014-11-26	
acetone	67-64-1	C	3 000 ppm	2014-11-26	
acetone	67-64-1	PEL	500 ppm 1 200 mg/m ³	2014-11-26	

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

8.2 Exposure controls
Personal protective equipment

- Eye protection : Goggles
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
 Recommended preventive skin protection
 Skin should be washed after contact.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice :

- : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.

:

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : liquid
- Colour : silver
- Odour : characteristic
- pH : substance/mixture is non-soluble (in water)
- Freezing point : No data available

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

Boiling point/boiling range	: 76 °C
Flash point	: -4 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1,08 g/cm ³
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

No data available

Skin corrosion/irritation**Product**

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product**

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may
degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

Additional ecological information : No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number**

ADR : 1263
TDG : 1263
CFR : 1263
IMDG : 1263
IATA : 1263

14.2 Proper shipping name

ADR : PAINT

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

TDG : PAINT
CFR : PAINT
IMDG : PAINT Classified according to 2.3.2.2 IMDG-Code
IATA : PAINT classified according to 3.3.3.1 IATA-DGR

14.3 Transport hazard class

ADR : 3
TDG : 3
CFR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packaging group : III
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

TDG
Packaging group : III
Labels : 3

CFR
Packaging group : III
Labels : 3

IMDG
Packaging group : III
Labels : 3

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

EmS Number : F-E, S-E

IATA

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packaging group : III

Labels : 3

14.5 Environmental hazards**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE A-41010 AE

Version 2.1

Revision Date 04.05.2021

Print Date 25.02.2022

SECTION 16: Other information**Full text of H-Statements**

H225 : Highly flammable liquid and vapour.
H228 : Flammable solid.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.