

**Date of impression** 09.04.2024/16:02:22  
**page/of** 1/1

**edition** 27.07.2022

**material denomination** METALURE L-55350  
**material-no.** 056252IA0  
**material description** Metalure Dispersion (PVD Pigment) in Ethyl Acetate  
 for Paints and Printing Inks  
 Stir before using !

**material specification**

<b>insp. characteristic</b>	<b>specification</b>	<b>unit</b>
Tl00138 Visual appearance (bar down)	pass	
Tl02003 D 10	4,0 - 6,0	µm
Tl02003 D 50	11,0 - 12,0	µm
Tl02003 D 90	<= 24,0	µm
Tl02015 pigment content / non volatile	9,95 - 10,15	%
Tl02021 acetone content	<= 3,0	%

total shelf life in month: 24

EC-safety data sheet-no. 056252IA0

Under storage & transportation conditions, a 1%-2% loss by weight is possible due to solvent evaporation. This minimum solvent loss will not impact the quality of this product.

The Data on this technical information sheet correspond with the current status of our knowledge and experience.

The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
27.07.2022	27.07.2022	27.07.2022

This document has been printed automatically and will not be signed.