

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : VP-72214/G 30 4 μ
Material number : 027434QQ0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Acute toxicity, Category 5, Oral, H303
Acute toxicity, Category 5, Dermal, H313

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Skin corrosion/irritation, Category 3, H316
 Serious eye damage/eye irritation, Category 2A, H319
 Specific target organ toxicity - single exposure, Category 3,
 Central nervous system, H336

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
 H303 + H313: May be harmful if swallowed or in contact with skin.
 H316: Causes mild skin irritation.
 H319: Causes serious eye irritation.
 H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing mist or vapours.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P301 + P332 + P317 IF SWALLOWED or if skin irritation occurs: Get medical help.
 P303 + P361 + P353 + P317 IF ON SKIN (or hair): Take off

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

immediately all contaminated clothing. Rinse skin with water.

Get medical help.

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P317 If eye irritation persists: Get medical help.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
propan-2-ol	67-63-0
1-methoxypropan-2-ol	107-98-2

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
propan-2-ol	67-63-0 200-661-7	Flam. Liq.;2;H225 Acute Tox.;5;H303	50 - 100

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

		Acute Tox.;5;H313 ;2A;H319 STOT SE;3;H336	
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	20 - 25
1-methoxypropan-2-ol	107-98-2 203-539-1	Flam. Liq.;3;H226 STOT SE;3;H336	1 - 10
salt of phosphoric acid (72243/00/2008.0040, Germany)	Not Assigned	;2;H315 ;2A;H319	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
 Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
 If on clothes, remove clothes.

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

- In case of eye contact : Immediately flush eye(s) with plenty of water.
Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Dry sand, Special powder against metal fire
- Unsuitable extinguishing media : Water, Foam, Carbon dioxide (CO₂), ABC powder
- High volume water jet

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Protect from humidity and water. Do not allow to dry.
- Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m ³	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is				

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

		no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
1-methoxypropan-2-ol	107-98-2	STEL	150 ppm 568 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skin Indicative			
1-methoxypropan-2-ol	107-98-2	TWA	100 ppm 375 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skin Indicative			
1-methoxypropan-2-ol	107-98-2	AGW	100 ppm 370 mg/m ³	2010-08-04	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

8.2 Exposure controls
Personal protective equipment

- Eye protection : Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
 Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
 Recommended preventive skin protection
 Skin should be washed after contact.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Long sleeved clothing
 Safety shoes
- : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- : In the case of dust or aerosol formation use respirator with an approved filter.

Environmental exposure controls

- General advice :
- : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Water : The product should not be allowed to enter drains, water courses or the soil.
- :
-

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : liquid
- Colour : silver
- Odour : characteristic
- pH : substance/mixture is non-soluble (in water)
- Freezing point : No data available

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Boiling point/boiling range	: 82 °C
Flash point	: 12 °C
Bulk density	: No data available
Flammability (solid, gas)	: The substance or mixture is a flammable solid with the category 1.
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air. Not explosive Vapours may form explosive mixture with air.

9.2 Other information

No data available

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Other information : No data available

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****propan-2-ol :**

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

1-methoxypropan-2-ol :

Acute oral toxicity : LD50 Rat: 4 016 mg/kg

Acute inhalation toxicity : LC50 Rat: > 25,8 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

VP-72214/G 30 4μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may
degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

VP-72214/G 30 4μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

ADR	: 1263
TDG	: 1263
CFR	: 1263
IMDG	: 1263
IATA	: 1263

14.2 Proper shipping name

ADR	: PAINT
TDG	: PAINT
CFR	: PAINT
IMDG	: PAINT

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

IATA : PAINT**14.3 Transport hazard class****ADR** : 3**TDG** : 3**CFR** : 3**IMDG** : 3**IATA** : 3**14.4 Packing group****ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

Tunnel restriction code : (D/E)

TDG

Packaging group : II

Labels : 3

CFR

Packaging group : II

Labels : 3

IMDG

Packaging group : II

Labels : 3

IATAPacking instruction (cargo
aircraft) : 364

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

Packing instruction : 353
(passenger aircraft)

Packing instruction (LQ) : Y341

Packaging group : II

Labels : 3

14.5 Environmental hazards

14.6 Special precautions for user

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Banned and/or restricted
(propan-2-ol)
(aluminium powder (stabilised))

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022

(1-methoxy-2-propanol)
(salt of phosphoric acid
(72243/00/2008.0040, Germany))

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H228 : Flammable solid.
H303 : May be harmful if swallowed.
H303 + H313 : May be harmful if swallowed or in contact with skin.
H313 : May be harmful in contact with skin.
H315 : Causes skin irritation.
H316 : Causes mild skin irritation.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

VP-72214/G 30 4 μ

Version 1.0

Revision Date 07.11.2022

Print Date 08.11.2022
